

OFFICIAL TECHNICAL DATASHEET

WG815WH

WG815WH Wheeled Excavator

Hydraulic wheeled excavator · 9 t · 66 kW Yuchai engine · load-sensing hydraulics · 30 km/h travel speed



OPERATING WEIGHT

9 t

ENGINE POWER

66 kW

BUCKET CAPACITY

0.45 m³

MAX. TRAVEL SPEED

30 km/h

BRAND

WIMER

MODEL

WG815WH

CATEGORY

Excavators

MODEL YEAR

2026

9-tonne wheeled excavator built for urban works, road maintenance and job sites that demand fast on-road travel between fronts. High-efficiency, low-consumption 66 kW Yuchai YC4DK90-T304 engine, load-sensing hydraulic system that cuts displacement losses and energy use, and a reinforced side-reduction axle designed for heavy-duty service. Enlarged safety cab with ergonomic design, hydraulic brakes with high-precision electric controls, 0.45 m³ bucket and a 30 km/h top travel speed. Wide range of attachments available, adaptable to different working conditions.

01 ENGINE

Manufacturer	Yuchai	Rated speed	2 000 rpm
Engine model	YC4DK90-T304	Max. torque	358 N·m
Rated power	66 kW		

02 PERFORMANCE PARAMETERS

Total weight	9 000 kg	Min. turning radius	1 930 mm
Bucket capacity	0.45 m ³	Front axle oscillation range	±7°
Tyre model	8.25-20	Shift mode	Electric shift control
Max. travel speed	30 km/h	Braking system	Hydraulic brake
Theoretical gradeability	35°	Fuel tank capacity	166 L
Swing speed	0 – 12.5 rpm		

03 HYDRAULIC SYSTEM

Main pump	Load-sensing pump	System pressure	28 MPa
Pilot pump	Pressure relief valve	Hydraulic tank capacity	120 L
Main pump max. flow	210 L/min		

WIMER GLOBAL · SALES & SUPPORT

WIMER manufactures and directly supports its full heavy machinery line. For quotes, availability and spare parts, contact us via WhatsApp, phone or email.

WEBSITE

www.wimerglobal.com

EMAIL

support@wimerglobal.com

WHATSAPP

+593 98 572 6302

FACTORY · CHINA

+86 10 8783 3628

SALES & DISTRIBUTION · ECUADOR

+593 96 140 0199

ADDRESS

Union Building, No. 2 Eqiao Rd.,
Sanshan District, Wuhu, Anhui,
China

Technical notice. The specifications listed correspond to the model's standard configuration. WIMER reserves the right to modify components or configurations for continuous improvement or homologation. Declared weights, dimensions and performance figures are nominal; images are illustrative and final trim may vary by unit and optional equipment. Warranty: 12 months or 2,000 operating hours, whichever comes first.